



"WE MAKE THE KITCHEN BETTER!"

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com

California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

Top Mount Reach-In Refrigerators

Standard Features

- Top mount compressor with environmentally friendly R290 refrigerant
- Stainless steel exterior & interior
- Electronic temperature controller
- Maintains temperatures between 35°F – 38°F
- LED interior light(s)
- Recessed door handle(s)
- Door lock(s) standard
- Magnetic door gasket(s) standard for positive door seal
- Pre-installed casters
- Three (3) pre-installed shelves per section
- Down duct refrigeration to ensure even distribution of air
- Wall bracket standard for MBF15RSGR(L) and is required for use

Optional Accessories

- Extra shelves – includes 4 shelf clips per shelf
MBF15RSGR(L) shelf part #: R060040000003
MBF8004GR(L) shelf part #: W0402389
MBF8005GR shelf part #: W0402385
MBF8006GR shelf part #: W0402385 left/right shelf,
part #: W0402386 middle shelf

For the best results of food preservation we recommend setting your refrigerator between 35°F to 38 °F

1. Don't forget to leave the unit some room to breathe!
2. Please clean the condenser frequently to give the unit more fresh air.

MODELS:

**MBF15RSGR / MBF15RSGRL / MBF8004GR
MBF8004GRL / MBF8005GR / MBF8006GR**



MBF15RSGR MBF15RSGRL MBF8004GR



MBF8004GRL

MBF8005GR



MBF8006GR



**2 YEAR PARTS AND LABOR WARRANTY
5 YEAR COMPRESSOR PART WARRANTY**



MBF8004GR(L)
MBF8005GR
MBF8006GR



REV. 09/25



"WE MAKE THE KITCHEN BETTER!"

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com


California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

SPECIFICATIONS


Models	Door	Capacity (Cu.Ft.)	Shelves	Casters (inch)	Rated Current (A)	Voltage (V/Hz/Ph)	HP	Refrigerant	Exterior Dimensions (inch)	Net Weight (lb)	Gross Weight (lb)
MBF15RSGR	1	13	3	4	2.1	115/60/1	1/7	R290	17 ^{3/4} ×37×81 ^{1/2}	192	270
MBF15RSGRL	1	13	3	4	2.1	115/60/1	1/7	R290	17 ^{3/4} ×37×81 ^{1/2}	192	270
MBF8004GR	1	21.4	3	4	2.1	115/60/1	1/7	R290	28 ^{3/4} ×31 ^{3/4} ×81 ^{3/8}	220	254
MBF8004GRL	1	21.4	3	4	2.1	115/60/1	1/7	R290	28 ^{3/4} ×31 ^{3/4} ×81 ^{3/8}	220	254
MBF8005GR	2	43.2	6	4	3.2	115/60/1	1/5	R290	51 ^{3/4} ×31 ^{3/4} ×81 ^{3/8}	340	390
MBF8006GR	3	64.9	9	4	4.2	115/60/1	1/4	R290	77 ^{3/4} ×31 ^{3/4} ×81 ^{3/8}	472	551

PLAN VIEW


MBF8004GR





MBF8004GRL







MBF8005GR



MBF8006GR






*Interior Dimensions






SELF-CLOSING
AND STAY OPEN
DOOR FEATURE

MBF15RSGR



MBF15RSGRL




Casters

Epoxy shelves


Door lock

Down duct

Temperature control



NEMA 5-15P



NEMA
15A/125V